



# EPOXY FILLER

## PRODUCT DATA SHEET

Two Part

Epoxy glue specially formulated for use as a gap filler in floors.

### Directions for Use

Accurately mix two volumes of Part A with one volume of Part B and stir thoroughly to avoid gelation in pot. Mix only as much as can be applied in 10 minutes.

**To colour filler**, add fine sanding dust of the same floor type or oxide and stir in thoroughly.

Filler should be firm after overnight cure in summer conditions.

Full strength will be achieved after 48 hours. Allow longer in cooler conditions.

### Warning

This substance may be harmful if swallowed, inhaled or absorbed through the skin. It may cause sensitising response.

Use with adequate ventilation and do not breathe vapours. Avoid contact with skin and eyes by use of impermeable gloves and goggles. Store containers in a cool well-ventilated area away from sources of heat and away from foodstuffs. Dispose of container in approve facility.

Spillages: Wear solvent-proof gloves, goggles and boots.

Absorb with sand or sawdust. **DO NOT** allow to enter drains.

Fire: Wear breathing apparatus. Use dry powder Co2 or foam.

### First Aid

Ingestion: **DO NOT** induce vomiting. Give 250ml water to drink.

Skin: Wash with soap and water at first opportunity.

Eyes: Wash with running water for at least 15 minutes.

**Get medical attention if symptoms persist.**